

# MATERIAL SAFETY DATA SHEET

## RED TEK® FUEL ENHANCER™

### SECTION 1 - IDENTIFICATION

**MANUFACTURER:** Thermofluid Technologies, Inc.  
**ADDRESS:** 409 Home Avenue  
Maryville, TN 37801  
**PHONE:** (865) 983-1633  
**FAX:** (865) 983-0068

**PRODUCT NAME:** RED TEK® FUEL ENHANCER™  
**PROPER SHIPPING NAME:** consumer commodity  
**UN NUMBER:** n/a  
**HAZARDOUS GOODS:** n/a  
**PACKING GROUP:** n/a

**CHEMTREC- TOLL FREE 24 HOUR EMERGENCY TELEPHONE NUMBER 1 – 888- 676-9380.**

### SECTION 2 – PHYSICAL PROPERTIES

**APPEARANCE:** Red colour: alcohol odour  
**ODOUR THRESHOLD:** Very light viscous liquid, alcohol odor  
**COEFF.WATER/ OIL DIST:** 70% soluble  
**FREEZING POINT:** N/A  
**VAPOR DENSITY: (est.) (Air=1);**2.40  
**VAPOR PRESSURE: (mmHg)** 104@38°C

**PHYSICAL STATE:** Liquid  
**SOLUBILITY IN WATER:** 80  
**EVAPORATION RATE:** 2.14  
**BOILING POINT:** 189°F  
**pH:**N/A  
**SPECIFIC GRAVITY:** N/A

### SECTION 3 – FIRE OR EXPLOSION HAZARD

**AUTO – IGNITION TEMPERATURE:** N/A  
**FLASHPOINT:** 62°F      **LOWER FLAMMABLE LIMIT (LEL):** 2%      **UPPER FLAMMABLE LIMIT (UEL):** 12%

**EXTINGUISH MEDIA:** Foam, water fog, chemical, co2  
**HAZARDOUS COMBUSTION PRODUCTS:** Normal combustion forms oxides of carbon.  
**SENSITIVITY TO STATIC DISCHARGE:** N/A  
**EXPLOSION DATA:**N/A.  
**FIRE AND EXPLOSION HAZARD:** Respiratory protection(NIOSH approved) for fire fighting personnel. Cool with water.

### SECTION 4 – INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>%</u>	<u>CAS NUMBER</u>	<u>LD50</u>	<u>P.E.L.</u>	<u>ACGIH TLV</u>
ETHYL ALCOHOL	>10	64-17-5		1000	1000
ALIPHATIC ALCOHOL	>10	67-63-0		400ppm	
ALIPHATIC HYDROCARBONS	>5	8008-20-6			
PETROLEUM NAPHTHA	>5	8030-30-6			

**This product does not contain any chemical listed as a carcinogen by OSHA,IARC Monographs or the National Toxicology Program. Does not contain any ozone depleting substances or heavy metals and complies with the RCRA Clean Air Act of 1991.**

### SECTION 5 – REACTIVITY DATA

**CHEMICAL STABILITY:** This material is chemically stable.  
**CONDITIONS TO AVOID:** Avoid sparks, open flame or any source of ignition.  
**INCOMPATIBLE MATERIALS:** Avoid contact with strong oxidizing agents such as chlorine, permangantes and dichromate.  
**DECOMPOSITION PRODUCTS:** Burning of this product can produce oxides of carbon.  
**HAZARDOUS POLYMERIZATION:** Will not occur.  
**POLYMERIZATION TO AVOID:** None known.

## **SECTION 6-HEALTH HAZARD**

**INHALED / ASPHYXIAN:** Vapor irritates nose and throat.

**INGESTION:** May cause depression of central nervous system.

**EYE CONTACT:** Vapor irritates eyes.

**SKIN CONTACT:** Prolonged contact may irritate the skin.

## **SECTION 7-FIRST AID**

**INHALED:** Remove exposed person to fresh air and ventilate area.

**EYES:** Flush eyes with large quantities tepid water for 15 minutes and call a physician if irritation persists.

**SKIN:** Wash with soap and water.

**INGESTION:** In case of accidental ingestion do NOT induce vomiting, seek immediate medical attention. Never give anything by mouth to an unconscious person.

## **SECTION 8-SAFE HANDLING**

**SPILLS:** Eliminate ignition source. Prevent liquid from entering sewers, watercourses or low areas. Adequately ventilate area. Recover free liquid by pumping or use a suitable absorbent (vermiculite).

**WASTE DISPOSAL METHOD:** Dispose of product in accordance with local, county, state, and federal regulations.

**STORAGE, HANDLING, SHIPPING:** Keep container closed until ready for use. Store in cool, well ventilated area. Store away from heat, flame, and/or static discharge. Do NOT store above 120° F.

**OTHER PRECAUTIONS:** Do not store or handle in temperatures above 120° F.

## **SECTION 9-PERSONAL PROTECTION**

**WORK/HYGIENIC PRACTICES:** Use usual, good hygienic practices; wash thoroughly after use.

**EYES:** Wear chemical safety glasses with side shields and/or goggles.

**GLOVES:** Chemical resistant.

**OTHER PROTECTIVE CLOTHING:** Usually not needed.

**RESPIRATORY PROTECTION:** If ventilation of the area is not adequate, use a NIOSH approved respirator to prevent over exposure by inhalation.

## **SECTION 10-PREPARATION**

Thermofluid Technologies Inc. ; 409 Home Avenue, Maryville, TN 37801 865-983-1633 Prepared by Missy Simpson January 21, 2011 REV.

All information provided for this MSDS sheet by Thermofluid Technologies, Inc. is offered in good faith and is believed to be accurate to the best knowledge of the preparation analyst. The information contained in this document is based on documentation provided by the supplier and other documentation/information available at the date of preparation. Thermofluid Technologies, Inc. does not guarantee the accuracy of this document and this information is offered without warranty, guarantee or liability on the part of the preparation analyst in good faith.